



RECALL CAMPAIGN BULLETIN

Reference:

NTB14-034

Date:

May 1, 2014

VOLUNTARY SAFETY RECALL CAMPAIGN 2014 ROGUE AND PATHFINDER WHEEL LUG NUT TORQUE

CAMPAIGN ID #: PC274

APPLIED VEHICLES: 2014 Pathfinder (R42)
2014 Rogue (T32)

Check Service COMM to confirm campaign eligibility.

INTRODUCTION

Nissan is conducting a Voluntary Safety Recall Campaign on certain specific Model Year 2014 Nissan Rogue and Pathfinder vehicles to inspect the torque on the road wheel nuts (lug nuts). This service will be performed at no charge to owners for parts or labor.

IDENTIFICATION NUMBER

Nissan has assigned identification number PC274 to this campaign. This number must appear on all communications and documentation of any nature dealing with this campaign.

DEALER RESPONSIBILITY


It is the dealer's responsibility to check Service Comm for the campaign status on each vehicle falling within the range of this voluntary safety recall campaign which for any reason enters the service department. This includes vehicles purchased from private parties or presented by transient (tourist) owners and vehicles in a dealer's inventory. **Federal law requires that new vehicles in dealer inventory which are the subject of a safety recall must be corrected prior to sale. Failure to do so can result in civil penalties by the National Highway Traffic Safety Administration.** While federal law applies only to new vehicles, Nissan strongly encourages dealers to correct any used vehicles in their inventory before they are retailed.

Nissan Bulletins are intended for use by qualified technicians, not 'do-it-yourselfers'. Qualified technicians are properly trained individuals who have the equipment, tools, safety instruction, and know-how to do a job properly and safely. NOTE: If you believe that a described condition may apply to a particular vehicle, DO NOT assume that it does. See your Nissan dealer to determine if this applies to your vehicle.

SERVICE PROCEDURE

1. Place the vehicle in a level working area.
2. Make sure the transmission is in Park and the ignition is OFF.
3. Set the parking brake.
4. If needed, remove wheel covers.
5. Check and tighten the lug nuts (Road-Wheel Nuts) for all four wheels as follows:

- Tighten by dividing torque into two or three levels in order to prevent the wheels from developing any distortion.
- Use a diagonal pattern as shown while checking/tightening the lug nuts.
- Torque to 113 N·m (11.5 kg-m, **83 ft-lb**).
- If a lug nut (Road-Wheel Nut) is missing, replace it with one listed in the Parts Information.
- DO NOT tighten the lug nuts to a torque exceeding specification to prevent strain on the disc brake rotor.



6. If needed, re-install wheel covers.

PARTS INFORMATION

DESCRIPTION	PART NUMBER	QUANTITY
Nut Road-Wheel (for steel wheels)	40224-ZE73A	As needed
Nut Road-Wheel (for aluminum wheels)	40224-ZN50A	As needed

CLAIMS INFORMATION

Submit a Campaign (CM) line claim using the following claims coding:

CAMPAIGN ("CM") I.D.	DESCRIPTION	OP CODE	FRT
PC274	Torque lug nuts; if needed, replace lug nuts	PC2742	0.2 hrs.