

NHTSA#: 14V-XXX  
To be assigned

TC#: N/A

Job Code: 9902218  
Flat Rate: 0.3

---

---

**LABELS ARE INCLUDED WITH NOTIFICATION**

---

---

**ACTION REQUIRED:**

Replace the Federal Certification Label and Tire Label

**MODELS / UNITS:**

**2015 Starcraft Launch Travel Trailers WITH Extremem Package Option**

16RB F2JP5051 - F2JP5062

**KIT CONTENTS**

Labels are included with notification

Instruction sheet  
Tire Label  
Certification Label

**TOOLS/MATERIAL REQ.**

Isopropyl Alcohol  
Shop Rag

**Instructions**

**Remove existing label(s)**

Locate the label(s) on the outside off door side (road side) front of the unit. Remove the existing Federal Certification and Tire Label from the unit and discard them.

Using isopropyl alcohol and a shop rag, remove any adhesive residue from the surface where the original label had been. Allow the area to dry for at least 30 seconds.

**Apply new label(s)**

Remove the protective back from the new label (s). Align the new label in the same location of the original label and apply it to the surface. Remove any air bubbles from the label. Repeat this process for the remaining label.

**NOTE: Do not attempt to remove or adjust the label once it has come into contact with the surface.**

**Doing so may damage the label or cause it not to adhere properly to the surface. IF A LABEL IS DAMAGED OR WILL NOT PROPERLY ADHERE TO THE SURFACE, A NEW LABEL MUST BE ORDERED.**

# \*1SABS0BN4C28B5215\*

RESP MFR: **Starcraft** 09/11  
 FABRICANT RESP: V.I.N./N.I.V  
 GVWR:/PNBV KG **1SABS0BN4C28B5215** PRESS./COLD INFL.  
 SIZE/DIMENSION **7500 3405** PRESS./GONFL FROID

GAWR/PNBE KG	TIRE/PNEU	RIMS/JANTE	PSI/LPC	KPA
3500 1589 FRONT/DEVANT	ST205/75R15C 15 X 5 JJ		50	345
0000 INT/CENTRAL				0000
3500 1589 REAR/ARRIERE	ST205/75R15C15 X 5 JJ		50	0345

TYPE OF VEHICLE/TYPE DE VEHICULE:  
 THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S.  
 FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND  
 STANDARDS PRESCRIBED UNDER THE CANADIAN  
 MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT  
 ON THE DATE OF MANUFACTURE SHOWN ABOVE.

TRAILER/REMORQUE  
 CE VEHICULE CONFORME A TOUTES LES NORMES QUI  
 LUI SONT APPLICABLES EN VERTU DU REGLEMENT  
 SUR LA SECURITE DE VEHICULES AUTOMOBILES  
 DU CANADA ET DES ETATS UNIS EN VIGUEUR A LA DATE  
 DE SA FABRICATION CI -DESSUS.

Federal Certification Label

**TIRE AND LOADING INFORMATION**  
**RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT**

The weight of cargo should not exceed 732 kg or 1612 lbs.  
 Le poids du chargement ne doit jamais dépasser 732 kg ou 1612 lbs.

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID
FRONT AVANT	ST225/75R15D	449 KPA, 65 PSI
REAR ARRIERE	ST225/75R15D	449 KPA, 65 PSI
SPARE DE SECOURS	ST225/75R15D	449 KPA, 65 PSI

SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION  
 VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS

1SABS0BN4C28B5215

Tire Label