

NHTSA#: 14V-509

TC#: N/A

Job Code: 9902218

Flat Rate: 0.3

LABELS ARE INCLUDED WITH NOTIFICATION

ACTION REQUIRED:

Replace the Federal Certification Label and Tire Label

MODELS / UNITS:

2015 Starcraft Launch Travel Trailers WITH Extremem Package Option

16RB **F2JP5051 - F2JP5062**

KIT CONTENTS

Labels are included with notification

Instruction sheet
Tire Label
Certification Label

TOOLS/MATERIAL REQ.

Isopropyl Alcohol
Shop Rag

Instructions

Remove existing label(s)

Locate the label(s) on the outside off door side (road side) front of the unit. Remove the existing Federal Certification and Tire Label from the unit and discard them.

Using isopropyl alcohol and a shop rag, remove any adhesive residue from the surface where the original label had been. Allow the area to dry for at least 30 seconds.

Apply new label(s)

Remove the protective back from the new label (s). Align the new label in the same location of the original label and apply it to the surface. Remove any air bubbles from the label. Repeat this process for the remaining label.

NOTE: Do not attempt to remove or adjust the label once it has come into contact with the surface. Doing so may damage the label or cause it not to adhere properly to the surface. IF A LABEL IS DAMAGED OR WILL NOT PROPERLY ADHERE TO THE SURFACE, A NEW LABEL MUST BE ORDERED.

1SABS0BN4C28B5215

RESP MFR:
FABRICANT RESP:
GVWR:/PNBV KG

Starcraft
V.I.N./N.I.V

09/11

7500 3405

1SABS0BN4C28B5215
SIZE/DIMENSION

PRESS./COLD INFL.
PRESS./GONFL FROID

GAWR/PNBE KG

TIRE/PNEU

RIMS/JANTE

PSI/LPC

KPA

3500 1589 FRONT/DEVANT

ST205/75R15C 15 X 5 JJ

50

345

00000 INT/CENTRAL

0000

3500 1589 REAR/ARRIERE

ST205/75R15C15 X 5 JJ

50

0345

TYPE OF VEHICLE/TYPE DE VEHICULE:
THIS VEHICLE CONFORMS TO ALL APPLICABLE U.S.

FEDERAL MOTOR VEHICLE SAFETY STANDARDS AND
STANDARDS PRESCRIBED UNDER THE CANADIAN
MOTOR VEHICLE SAFETY REGULATIONS IN EFFECT
ON THE DATE OF MANUFACTURE SHOWN ABOVE.

TRAILER/REMORQUE
CE VEHICULE CONFORME A TOUTES LES NORMES QUI
LUI SONT APPLICABLES EN VERTU DU REGLEMENT
SUR LA SECURITE DE VEHICULES AUTOMOBILES
DU CANADA ET DES ETATS UNIS EN VIGUEUR A LA DATE
DE SA FABRICATION CI-DESSUS.

Federal Certification Label



TIRE AND LOADING INFORMATION RENSEIGNEMENTS SUR LES PNEUS ET LE CHARGEMENT

The weight of cargo should not exceed kg or lbs.
Le poids du chargement ne doit jamais dépasser 732 kg ou 1612 lb.

TIRE PNEU	SIZE DIMENSIONS	COLD TIRE PRESSURE PRESSION DES PNEUS A FROID	SEE OWNER'S MANUAL FOR ADDITIONAL INFORMATION
FRONT AVANT	ST225/75R15D	449 KPA, 65 PSI	VOIR LE MANUEL DE L'USAGER POUR PLUS DE RENSEIGNEMENTS
REAR ARRIERE	ST225/75R15D	449 KPA, 65 PSI	
SPARE DE SECOURS	ST225/75R15D	449 KPA, 65 PSI	

1SABS0BN4C28B5215

Tire Label