

**March 4, 2015**

01615-01646 Version 2

## Safety Recall: Connecting Rod

Supersedes 15-017, dated February 27, 2015, to revise the information highlighted in yellow.

### AFFECTED VEHICLES

Year	Model	VIN Range
2014–15	Accord L4	Check the iN VIN status for eligibility
2015	CR-V	Check the iN VIN status for eligibility

### REVISION SUMMARY

Under PARTS INFORMATION, a part number was added to the Accord L4 and CR-V parts list.

### BACKGROUND

During assembly of the short block, some connecting rod bolts may not have been properly torqued. If a connecting rod bolt was not torqued properly, the engine may rattle/knock, leak oil, or lose power, increasing the risk of a crash.

### CUSTOMER NOTIFICATION

Owners of affected vehicles will be sent a notification of this campaign.

Do an iN VIN status inquiry to make sure the vehicle is shown as eligible.

Some vehicles affected by this campaign may be in your new and used vehicle inventory. These vehicles must be repaired before they are sold.

Should a dealership sell an unrepaired vehicle that subsequently causes an injury or damage because of the recalled item, the dealership will be solely responsible to the damaged party, and will be required to defend and indemnify American Honda for any resulting claims. To see if a vehicle in inventory is affected by this campaign, do a VIN status inquiry before selling it.

### CORRECTIVE ACTION

Replace the short block.

### PARTS INFORMATION

#### Accord L4

Part Name	Part Number	Quantity
L4 Cylinder Block	10002-5A2-A01	1
Castle Nut (14 mm)	90363-S3V-A01	2
Control Valve Oil Seal	15832-RAA-A01	1
Cylinder Head Gasket	12251-5A2-A01	1
Drain Plug Washer (20 mm)	94109-20000	1
Exhaust Pipe Gasket	18212-T2F-A01	1

**CUSTOMER INFORMATION:** The information in this bulletin is intended for use only by skilled technicians who have the proper tools, equipment, and training to correctly and safely maintain your vehicle. These procedures should not be attempted by "do-it-yourselfers," and you should not assume this bulletin applies to your vehicle, or that your vehicle has the condition described. To determine whether this information applies, contact an authorized Honda automobile dealer.

Flange Bolt (12 x 139 mm)	90176-TA0-A01	1
Flange Bolt (10 x 35 mm)	90163-SDA-A01	1
Flange Bolt (10 x 25 mm)	90167-SAA-010	2
Flange Bolt (12 x 75 mm)	90396-S5A-010	2
Flange Bolt (10 x 34 mm)	90162-T2A-A00	4
Flange Bolt (12 x 33 mm)	90186-SDA-A00	2
Flange Bolt (14 x 150 mm)	90177-SDA-A00	2
Flange Bolt (14 x 135 mm)	90176-SDA-A00	2
Flange Bolt (12 x 25 mm)	95701-12025-08	2
Flange Bolt (10 x 30 mm)	90176-S5A-000	2
Flange Bolt (10 x 35 mm)	90164-S5B-000	1
Flange Bolt (12 x 65 mm)	90168-TA0-A00	2
Flange Bolt (10 x 30 mm)	90161-T2F-A01	3
<b>Fuel Joint Pipe</b>	<b>16012-5A2-315</b>	<b>1</b>
Head Cover Gasket	12341-5A2-A01	1
Intake Manifold Gasket A	17115-5A2-A01	4
Mass Nut (12 mm)	90371-T2F-A01	2
Oil Seal (43 x 58 x 7 mm)	91212-5A2-A02	1
O-Ring (9.5 x 1.9 mm)	91307-PLC-004	1
O-Ring (12.6 x 2.4 mm)	91305-5A2-A01	2
O-Ring	91304-5A2-A01	1
O-Ring	91311-5A2-A01	1
O-Ring (37.2 x 4.25 mm)	91314-PR7-A00	1
Pre-Chamber Gasket (57.5 – 58.5 mm)	18393-SS0-J30	1
Primary Converter Gasket	18115-5A2-A01	1
Sealing Washer (6 mm)	90442-R7G-000	1
Self-Lock Nut (8 mm)	90115-659-003	2
Self-Lock Nut (10 mm)	90212-SA5-003	6
Set Ring (28 x 2 mm)	44319-S84-300	2
Spindle Nut	90305-S3V-A11	2
Split Pin (3.0 x 22 mm)	94201-30220	2
Spool Valve Filter Assembly	15815-5A2-A01	1
Thermostat Case Seal	19322-5A2-A00	1

**CR-V**

<b>Part Name</b>	<b>Part Number</b>	<b>Quantity</b>
L4 Cylinder Block	10002-5LA-A00	1
Bolt (12-Point, 8 x 21 mm)	90113-S10-000	8
Control Valve Oil Seal	15832-RAA-A01	1
Cylinder Head Gasket	12251-5A2-A01	1
Drain Plug Washer (18 mm)	90471-PX4-000	1
Exhaust Pipe Gasket	18212-T2F-A01	1
Flange Bolt (8 x 14 mm)	95701-08014-08	2
Flange Bolt (10 x 29 mm)	90382-SH9-003	2
Flange Bolt (14 x 115 mm)	90175-S5A-000	1
Flange Bolt (12 x 38 mm)	90162-SYP-000	2
Flange Bolt (12 x 35 mm)	90168-S5A-000	6
Flange Bolt (12 x 88 mm)	90167-S5A-010	1
Flange Bolt (12 x 25 mm)	90182-S2H-000	2
Flange Bolt (14 x 80 mm)	90163-SWE-T00	2
Flange Bolt (14 x 135 mm)	90176-SDA-A00	4
Flange Bolt (12 x 97 mm)	90165-S04-000	1
Flange Bolt (14 x 80 mm)	90160-T1W-A00	1
Flange Bolt (12 x 40 mm)	90164-S5A-010	1
Flange Nut (14 mm)	90213-S5A-003	1
Flange Nut (12 mm)	90371-SAA-010	2
Fuel Joint Pipe	16012-5A2-315	1
Head Cover Gasket	12341-5A2-A01	1
Intake Manifold Gasket	17115-5A2-A01	4
O-Ring	91311-5A2-A01	1
O-Ring (37.2 x 4.25 mm)	91314-PR7-A00	1
Oil Seal (43 x 58 x 7 mm)	91212-5A2-A01	1
Pre-Chamber Gasket (57.5 – 58.5 mm)	18393-SS0-J30	1
Primary Converter Gasket	18115-5A2-A01	1
Self-Lock Nut (8 mm)	90115-659-003	2
Self-Lock Nut (10 mm)	90212-SA5-003	6
Set Ring (28 x 2.0 mm)	44319-S84-300	2
Spindle Nut	90305-S3V-A11	2
Split Pin (3.0 x 22 mm)	94201-30220	2
Spool Valve Filter Assembly	15815-5A2-A01	1
Thermostat Case Seal	19322-5A2-A00	1

## WARRANTY CLAIM INFORMATION

NOTE: Template IDs cannot be used because the quantity of part numbers exceeds the system limitations (10).

Operation Number	Description	Flat Rate Time	Defect Code	Symptom Code	Failed Part Number
1111BD	<b>Accord</b> – Replace the short block.	12.6 hrs	5NL00	JP200	10002-5A2-A01
1111BD	<b>CR-V</b> – Replace the short block.	10.0 hrs	5NL00	JP300	10002-5LA-A00

Skill Level: Repair Technician

## REPAIR PROCEDURE

Replace the short block. Refer to the applicable electronic service manual.

END